



OMIX-ADA, Inc.



Part # 12103.02

460 HORIZON DR. SUITE 400 | SUWANEE, GA 30024 | PHONE: 770-614-6101 | FAX: 770-614-6069 | info@omix-ada.com

Door Strap; JK, JL & JT

1. The Rugged Ridge door strap will install over the existing OE door strap. **NO CUTTING REQUIRED.**

Unplug the door harness from the vehicle following the owner's manual.



2. Remove the front loop of the check strap from the retaining hook.

NOTICE Use caution, as door could swing open and damage mirror and/or cowl.



3. Remove T30 Torx bolts from footman loop securing strap to door. Remove footman loop from OE strap.





OMIX-ADA, Inc.



Part # 12103.02

460 HORIZON DR. SUITE 400 | SUWANEE, GA 30024 | PHONE: 770-614-6101 | FAX: 770-614-6069 | info@omix-ada.com

Door Strap; JK, JL & JT

4. Start zipper on vehicle side and zip fully (make sure tabs on OE straps are flat).

Zipper should be facing down for final installation.



5. Insert footman loop in desired slot and reinstall to the door.



6A. Tuck zipper pull behind door panel.

2007-2010 (JK) - Will secure without panel removal.

Reinstall factory screws once zipper pull is secured.





OMIX-ADA, Inc.



Part # 12103.02

460 HORIZON DR. SUITE 400 | SUWANEE, GA 30024 | PHONE: 770-614-6101 | FAX: 770-614-6069 | info@omix-ada.com

Door Strap; JK, JL & JT

6B. Tuck zipper pull behind door panel.

2011-2018 (JK) - Remove 2 T25 Torx screws form corner.

Reinstall factory screws once zipper pull is secured.



6C. Tuck zipper pull behind door panel.

2018+ JL (20+ JT) - Remove one lower T25 screw closest to strap.

Reinstall factory screws once zipper pull is secured.



7. Slide desired loop back onto factory retainer hook and reconnect door harness.

