



Installation Instructions: Fold & Tumble Rear Seat (1976-1995) CJ - YJ (13462.XX)

(Step 1 – Fig. A) Front Seat Brackets.

Remove seat mounting bolts from floor. Please note that some early CJ models may only have one mounting hole for each side. Drilling of the second mounting hole will be required (additional hardware supplied by customer). Grade 5 or higher bolt and large washer are recommended.

Install front seat brackets through seat mounting tabs as shown. Install C-clip to secure bracket to tab. Align mounting bracket over holes in floor and securely tighten with seat mounting bolts.

(Step2 – Fig.B) Rear Seat Lock

Remove seat belt anchor bolt from floor. Position lock underneath seat belt & eyelets as shown in (Fig.B). Please note that more than one hole is supplied to align the bracket with the floor mounting hole and seat lock. If desired an additional hole can be drilled and the bracket secured with two bolts. Grade 5 or higher bolt and large washer is recommended (supplied by customer). Reinstall seat belt anchor bolt through seat belt eyelets and seat lock. **DO NOT TIGHTEN YET.**

Align seat lock with striker so that seat locks when the seat is pushed down into position. Tighten seat belt anchor bolt. At this time a second hole, if desired, can be drilled and additional hardware added (supplied by customer).

