

Roll Bar Top, YJ

Included Components: 1-Brief
2-J-Clips

If your Wrangler does not have a soft top Windshield Channel, your installation requires the purchase of an aftermarket Windshield Channel (Part # 13308.01)

INSTALLATION INSTRUCTIONS:

Before you begin, the temperature of the Brief should be above 70 degrees Fahrenheit. We suggest laying the Brief in the sunlight for 1 hour before installation.

1. Locate the front edge and fold over (Figure 1).

Figure 1



2. Place the Brief on top of Jeep. Insert folded edge into Windshield Channel, working from one side of vehicle to the other (Figures 2 & 3).

Figure 2



Figure 3



3. Locate the Velcro straps on each side of the roll bar. Wrap the flaps around the roll bar and fasten (Figures 4 & 5). Do both driver and passenger sides of the vehicle.

Figure 4



Figure 5



NOTE: The rear straps can be fastened in two different methods:

Option 1 shows how to attach the Brief to your vehicle using J-Clips.

Option 2 shows how to attach the Brief to your vehicle around the rear shoulder seat belts.

Option 1 (with J-Clip)

4. Feed the rear corner straps through the J-Clips (Figure 6) and place the J-Clip under a convenient attachment point, such as a rear corner rail or floor loop (Figure 7).

Figure 6



Figure 7



5. Wrap the straps around the roll bar or seat belt shoulder harness. Feed the loose end through the buckle and pull tight (Figure 8). Be sure not to interfere with the seat belts safety and operation. Place the strap under the seat belt. Never install over the seat belt strap.

Figure 8



6. Re-adjust Velcro and tighten all straps to assure a wrinkle-free fit.

Option 2 (without J-Clip)

7. Wrap the straps around the seat belt shoulder harness and roll bar. Feed the loose end through the buckle on the other end and pull tight (Figure 9). Be sure not to interfere with the seat belts safety and operation. Place the strap under the seat belt. Never install over the seat belt strap.

Figure 9



8. Re-adjust Velcro and tighten all straps to assure a wrinkle-free fit.