



INSTALLATION INSTRUCTIONS

Part Number 33-2040

This filter fits: See current K&N catalog for complete listing

FREE K&N DECAL** To register your warranty, please see us online at knfilters.com/register. **FREE K&N DECAL

Congratulations, you have purchased the finest air filter that money can buy. With proper care, this filter can last 1 million miles or more. This filter is a direct replacement for the stock air filter, and no modifications will be required.

With the filter positioned in the airbox, the lid should be slid into place, (it may be necessary to remove the intake hose that runs from the airbox to the engine). Make sure that the tabs on the lid are inserted completely into the airbox slots. Hold pressure on the lid as the clamps are tightened so that it does not slide out of the tab slots. Do not use any grease on the filter as this will allow the lid to slide out of the tab slots. The intake hose may now be reinstalled if necessary.

THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SERVICED, OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE ENGINE COULD RESULT.

• 1455 CITRUS AVE., P.O. BOX 1329, RIVERSIDE, CA., U.S.A. 92502 • TECH SERVICE 800-858-3333 • FAX 909-684-9060
• e-mail: tech@knfilters.com • WWW: <http://www.knfilters.com>

17749



INSTALLATION INSTRUCTIONS

Part Number 33-2040

This filter fits: See current K&N catalog for complete listing

FREE K&N DECAL** To register your warranty, please see us online at knfilters.com/register. **FREE K&N DECAL

Congratulations, you have purchased the finest air filter that money can buy. With proper care, this filter can last 1 million miles or more. This filter is a direct replacement for the stock air filter, and no modifications will be required.

With the filter positioned in the airbox, the lid should be slid into place, (it may be necessary to remove the intake hose that runs from the airbox to the engine). Make sure that the tabs on the lid are inserted completely into the airbox slots. Hold pressure on the lid as the clamps are tightened so that it does not slide out of the tab slots. Do not use any grease on the filter as this will allow the lid to slide out of the tab slots. The intake hose may now be reinstalled if necessary.

THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SERVICED, OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE ENGINE COULD RESULT.

• 1455 CITRUS AVE., P.O. BOX 1329, RIVERSIDE, CA., U.S.A. 92502 • TECH SERVICE 800-858-3333 • FAX 909-684-9060
• e-mail: tech@knfilters.com • WWW: <http://www.knfilters.com>

17749