

# INSTALLATION MANUAL

PRODUCT: RIVAL HOOKS FOR BUMPER

MODEL: JEEP WRANGLER JK (2007-2018)  
JEEP WRANGLER JL (2018-)  
JEEP GLADIATOR JT (2019-)

PART NO: 2D.2715.1.4



## CAUTION!

To reduce the risk of serious injury or damage, please read and understand all instructions and procedures before attempting to install or use this product. Safety glasses must be worn at all times during installation or maintenance of this product. Ensure all mounting bolts are tensioned after 250 miles (400 km) and periodically thereafter.

## NOTICE

Whilst the hooks add additional protection to your vehicle, precautionary measures still need to be taken to avoid damage.  
Always drive to the conditions and your surroundings.

# HOOKS FOR BUMPER



Part number: 2D.2715.1.4

Suited to: JEEP WRANGLER JK 2007-2018  
JEEP WRANGLER JL 2018-  
JEEP GLADIATOR JT 2019-



## SAFETY NOTICE

- \* The RIVAL Hooks is designed to compliment the use and design of the specified vehicle under conditions specified by the vehicle manufacturer.
- \* While driving the vehicle at any speed, collision with any other vehicle, animal or object must always be avoided.
- \* Following any collision with any other vehicle, animal or object, the RIVAL Hooks and the vehicle must be inspected by a specialized or suitably qualified vehicle repairer for possible damage to the components and assemblies in order to confirm suitability for further use of the vehicle.
- \* It is strongly recommended that you do not operate a vehicle with a damaged Hooks or its components. In the case of damage, please contact the nearest RIVAL dealer. Vehicle, or where the Hooks has been damaged, is extremely dangerous and must be avoided at all cost.
- \* The operation of a vehicle where the Hooks is not properly attached and fastened to the vehicle, or where the Hooks has been damaged, is extremely dangerous and must be avoided at all cost.
- \* It is recommended that you carry out regular inspections of all the Hooks elements such as all bolts, wires, connectors.

## INSTALLATION NOTICE

- \* Personal safety during the installation process must be adhered to at all times and the use.
- \* Estimated time for installation: 30 minutes.
- \* The RIVAL Hooks must be mounted and affixed to the vehicle according to this installation manual of personal safety equipment is highly recommended.
- \* Do not install this Hooks on vehicle models other than those allowed in this manual.
- \* Check state and local highway safety laws regarding permitted bumper types and heights.

## REQUIRED TOOLS

- \* Basic tool kit
- \* Torque wrench
- \* Crosspoint and flat head screwdriver

## TORQUE SETTING

- M8 - 24 Nm (17.7 lb/ft)
- M12 - 77 Nm (56.8 lb/ft)

# PARTS LISTING



**Parts list:**

1. Tow hooks..... Qty 2

**Hardware list:**

A. Bolt M12x40..... Qty 6

B. Washer 12 mm..... Qty 6

# INSTALLATION PROCEDURE



Fig. 1

1. Unscrew 4 screws and remove steel bumper body, as shown in fig.1.

**\*Set aside for re-use later on.**



Fig. 2

2. Install tow hooks (item 1) on brackets . Fix it using bolts M12x40 (item A) and washer 12 mm (item B) (Fig. 2).

**\*Tighten hardware after that.**



Fig. 3

3. Install steel bumper body, using screws from step 1 (Fig. 3).

**\*Tighten hardware after that.**

# INSTALLATION PROCEDURE



Before operating a vehicle fitted with RIVAL Bumper:

- make sure all fittings are tightened
- check winch operation
- check all electrical wiring attached to lights



**Thank you for your choice!**

**Sincerely,  
RIVAL 4x4 Team**