


For installation of billet grilles that require cutting of the stock shell, proper tools, knowledge and skill are needed. Carriage Works is not responsible for care & accuracy of the installation, only for Fit & Finish of its products. Use a qualified installer or contact original vendor for references to complete all instructions.

Step 1: Center billet grille in opening. Use supplied hardware and attach per illustration below. Use Fig. 1 for horizontal bars and use Fig. 2 for honeycomb insert.

Step 2: Check to make sure the grille is properly in place and tighten the bolts just enough to hold the grille in place. **DO NOT OVER TIGHTEN** as this may cause the grille shell to crack.




Note: Please adjust horizontal blades if irregular. This is the result of shipping and handling outside of Carriage Works control. Carriage Works recommends applying a high quality automotive wax to maintain the original appearance.



41631 / 41632 / 41633 1999-01 Dodge Ram Full Size – Bolt Over

Step 1: Center billet grille in opening. Use supplied hardware and attach per illustration below. Use Fig. 1 for horizontal bars and use Fig. 2 for honeycomb insert.

Step 2: Check to make sure the grille is properly in place and tighten the bolts just enough to hold the grille in place. **DO NOT OVER TIGHTEN** as this may cause the grille shell to crack.



Note: Please adjust horizontal blades if irregular. This is the result of shipping and handling outside of Carriage Works control. Carriage Works recommends applying a high quality automotive wax to maintain the original appearance.