

CHEVROLET SILVERADO QUAD CAP INSTALLATION INSTRUCTIONS

Please read instructions thoroughly before installation.

Contents

Bed Rail Caps (4 pieces total)

- Driver Side Front (DS-F)
- Driver Side Rear (DS-R)
- Passenger Side Front (PS-F)
- Passenger Side Rear (PS-R)

(Please note that the Rear Pieces install toward the tailgate of the truck and the Front Pieces install toward the Cab).

Stake Pocket Covers (4 pieces total)

- Driver Side Front Cap (DS-FC)
- Driver Side Rear Cap (DS-RC)
- Passenger Side Front Cap (PS-FC)
- Passenger Side Rear Cap (PS-RC)

(Please note that the Stake Pocket Covers come pre-installed in each Quad Cap).

Test Fit Before Installation

Dry fit the Quad Caps without removing the adhesive tape liner to verify the correct position of each piece. Make sure that each piece fits snug against the bed rail and that there is no interference with a bed liner or bed cover.

Vehicle Preparation

1. Clean the bed rails where the Quad Caps are to be installed. Remove all dirt and debris and do not leave a residue. We recommend a Prep Sol or similar type cleaner, a wax and grease remover or a 50/50 blend of isopropyl alcohol and water.
2. Dry using a lint free cloth and inspect application area to be sure all moisture and residue has been removed.

Installation of Quad Caps

1. Installation temperature should be between 60°F and 95°F.
2. Install the rear pieces first (DS-R, PS-R).
3. Turn one of the Rear Caps over and remove the tape liner (red), exposing the grey acrylic tape. See Fig 1.



Figure 1.

Caution: This is pressure sensitive tape and will adhere aggressively to any surface in which it contacts.

4. Lightly place the cap on the back end of the bed rail making sure that the back end and the inside of the Quad Cap is flush with the back end (tailgate side) and the inside (bed side) of your vehicles bed rail.
5. Once you are satisfied with the placement, press down firmly on the Quad Cap moving from the back end to the front end of the bed rail making sure that all of the pressure sensitive tape is in contact with the bed rail. See Fig 2.



Figure 2.

6. Repeat steps 3 thru 5 for the other Rear Cap.
7. Turn one of the Front Caps over and remove the tape liner (red).
8. Starting from the front end of the installed Rear Cap, lightly place the Front Cap over the Rear Cap making sure to align and seat the last rib of the Front Cap over and flush with the end of the installed Rear Cap. Also, make sure the inside of the Front Cap is flush with the inside of the bed rail. Fig 3.



Figure 3.

9. Once you are satisfied with the placement, press down firmly on the Quad Cap moving from the back end to the front end of the bed rail making sure that all of the pressure sensitive tape is in contact with the bed rail. See Fig 4.



Figure 4.

10. Repeat steps 7 thru 9 for the other Front Cap.

Stake Pocket Removal

To remove a stake pocket cover simply install the end of a flat head screwdriver into the stake pocket removal slot and lightly pry upwards until one end of the stake pocket cover pulls free of the Quad Cap. Fig 5.



Figure 5.

Stake Pocket Installation

1. To install a stake pocket cover, make sure that the cover and cap rib patterns align... DS-FC installs in the Driver side-Front position, etc. Insert one of the stake pocket cover tabs into the corresponding slots in the Quad Cap, lightly bend the cover and insert the tab on the other side of the stake cover into the corresponding Quad Cap slot. Fig 6.



Figure 6.

If you have any questions or concerns about the application or installation please call us at 1-800-344-8759.

HUSKY LINERS PRODUCT WARRANTY

Husky Liners guarantees to the original purchaser of Husky Liners products that they will not break or tear under normal usage during the life of the motor vehicle in/on which they are installed. This warranty shall only be effective while the original purchaser owns the motor vehicle and shall not apply to Husky Liners products that have been removed from the original vehicle on which they were installed. This warranty applies only to those parts that are correctly installed in/on the vehicle for which they were intended.

Husky Liners will warrant any part during the warranty period that proves defective in material and/or workmanship under normal installation, use, service, or maintenance. Return alleged defective part to the place of purchase for replacement or refund. Please have a copy of your purchase receipt available when you call. The foregoing is the only express warranty made by the manufacturer and is limited to the duration of this warranty. **ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE IS LIMITED IN DURATION TO THE DURATION OF THIS WARRANTY. LABOR CHARGES, INJURIES, OR ANY OTHER LOSS OR DAMAGES WHATSOEVER, INCLUDING THOSE INCURRED IN INSTALLATION ARE EXCLUDED. ADDITIONALLY, PAINTING OF REPLACEMENT HUSKY LINER PARTS AND ANY VEHICLE COMPONENT REPAIR OR REPLACEMENT AS WELL AS INCIDENTAL DAMAGES ARE EXCLUDED.**

This warranty is void for damages to the product due to misuse, abuse, neglect, accident, improper installation or any use that violates the instructions furnished by us.

ABNORMAL WEAR AND TEAR ARE NOT COVERED UNDER THIS WARRANTY. Obviously, if your dog chews up your Husky Liner product, it's not covered under the warranty. Likewise, if you shut your Husky Liner in the door of your vehicle, damage to the liner and/or door are not covered. Commonplace, everyday wear on a particular product is considered normal, and is not covered under warranty repair.

**Winfield Consumer Products – 800.344.8759 – P.O.
BOX 839 – 22425 'D' St.– Winfield KS 67156**