

# CHOOSING THE CORRECT TIE DOWN







**HIGHLAND**® has a tie down for all of your carrying needs. See the chart below to determine which tie down is right for you.



## 1

### Determine Your Duty Level

	<b>LIGHT</b>	<b>STANDARD</b>	<b>HEAVY</b>	<b>SUPER</b>
<b>Description</b>	Secure light cargo up to 330 lb (total wt.) for short trip transport.	Secure light cargo up to 660 lb (total wt.) in truck bed or on light duty trailer.	Secure heavier loads up to 1660 lb (total wt.) such as touring motorcycle.	For the serious professional to secure cargo loads up to 3300 lb (total wt.).
<b>Towing or Carrying Vehicle</b>	Pickup truck, SUV, Car top racks	Pickup truck, Light duty trailer	Full size pickup truck, SUV, Car top racks	Gooseneck trailer, Heavy duty trailer, Flat bed trailer
<b>Types of Cargo</b>	Luggage, Lawnmower, Kayak, Bicycle, Snow Thrower	Motorcycle, Light fishing boat, Jet ski, Snowmobile	Motorcycle, Light fishing boat, Jet ski, Snowmobile, Lawn tractor	Ski boat, Small car, Heavy equipment
				

## 2

### Select the Necessary Length

Don't come up short! Consider the total length over your cargo to each connecting point.

## 3

### Choose the Appropriate Lever and Holding Force




#### QUANTITY and LENGTH



Measure distance between connection points and choose the appropriate length.



Use four or more straps for loads OVER 500 lb.

<b>CAMBUCKLE</b> Quick and easy to use... just press and pull tight	
<b>SURELOK</b> Locking Cam buckle combines ease of use with ratchet holding power	
<b>RATCHET</b> SUPER-strong holding power with vise-like grip and precise tension adjustment to secure all loads	

TIGHT TIGHTEST

TIGHT TIGHTEST

TIGHT TIGHTEST