## 14090

## CHEVY/GMC VAN SAVANA/EXPRESS (FULL SIZE)

6/14/2012

GROSS LOAD CAPACITY WHEN USED AS A WEIGHT CARRYING HITCH: 10,000 LBS. TRAILER WEIGHT & 1,000 LBS. TONGUE WEIGHT. GROSS LOAD CAPACITY WHEN USED AS A WEIGHT DISTRIBUTION HITCH: 12,000 LBS. TRAILER WEIGHT & 1,200 LBS. TONGUE WEIGHT

## \*\*\*DO NOT EXCEED VEHICLE MANUFACTURER'S RECOMMENDED TOWING CAPACITY.\*\*\*

$\overline{}$		DO NOT EXC		- COMMENDED TOWNS CAPACITI.
			Parts List	
ITEM	QTY		DESCRIPTION	_
1	6	HFN 1213	HEX FLANGE NUT	$\dashv$ $\Theta$
2	6	CM-SP1	.250 x 1.50 x 2.00" SQUARE HOLE SPACER	↓
3	6	1/2-13 x 1 3/4	CARRIAGE BOLT	
INS INS	TALL TI	GHT: <u>49</u> LBS. ME: <u>20</u> MINUTES	3	FRAME RAIL  EXISTING HOLE

## **INSTALLATION STEPS**

- 1) Raise hitch into position.
- 2) Using existing frame slots insert a 1/2" carriage bolt & spacer through each of the frame holes and into hitch. Fasten using a 1/2" flange nut as shown.
- 3) Torque to 110 lb.-ft.

PERIODICALLY CHECK THIS RECEIVER HITCH TO ENSURE THAT ALL FASTENERS ARE TIGHT AND THAT ALL STRUCTURAL COMPONENTS ARE SOUND.

Curt Manufacturing Inc., warrants this product to be free of defects in material and/or workmanship at the time of retail purchase by the original purchaser. If the product is found to be defective, Curt Manufacturing Inc., may repair or replace the product, at their option, when the product is returned, prepaid, with proof of purchase. Alteration to, misuse of, or improper installation of this product voids the warranty. Curt Manufacturing Inc.'s liability is limited to repair or replacement of products found to be defective, and specifically excludes liability for incidental or consequential loss or damage.