



TEL: 1-866-XANATOS

INSTALLATION INSTRUCTIONS

**TAIL LIGHT GUARD FOR JEEP LIBERTY 08-10
PART # 7JP406SS/7JP406A**



PARTS LIST:

1	Driver/Left Taillight Guard	2	4mm -.7x 16mm Sheetmetal Screws
1	Passenger/Right Taillight Guard	2	4mm Lock Washers
2	Support Brackets	2	4mm ID x 9mm OD x 1mm Flat Washers

PROCEDURE:

- 1. REMOVE CONTENTS FROM BOX. VERIFY ALL PARTS ARE PRESENT. READ INSTRUCTIONS CAREFULLY BEFORE STARTING INSTALLATION.**
- 2. IMPORTANT!** Cover the finish edge around the taillight housing with masking tape to protect the finish of the vehicle when removing the taillight housing and installing the Taillight Guard.
- Open the rear door and remove the driver's side screws holding the taillight housing **(Figure 1)**.
- Grasp the taillight housing with one hand and pull with your other hand gently. **NOTE:** Be sure to pull straight out towards the rear of the vehicle to avoid possible damage. This is the same procedure required to change a burn out taillight bulb in the assembly. For more info see owner's manual on replacing burn taillight bulbs.
- Once you have removed the taillight housing, carefully disconnect the wire harness and set aside.
- Remove the upper locating stud from taillight using a T20 torx wrench. Attach one of the Support Brackets to taillight by using the factory locating stud **(Figure 2)**. Reconnect the wire harness and then snap taillight back into place. **NOTE:** The bend end of the Support Bracket should be facing the rear of the vehicle **(Figure 3)**. Fully tighten at this time.
- Position Taillight Guard over taillight and attach it to vehicle using the factory hardware **(Figure 4)**.
- Attach the Taillight Guard to Support Bracket using the included (1) 4mm x 15mm Phillips Screws, (1) 4mm Lock Washer, and (1) 4mm Flat Washer **(Figure 5)**.
- Adjust Taillight Guard properly, and then tighten all hardware at this time.
- Repeat steps 2 – 9 for passenger side Taillight Guard.
- Do periodic inspections to the installation to make sure that all hardware is secure and tight.

To protect your investment, wax this product after installing. Regular waxing is recommended to add a protective layer over the finish. Do not use any type of polish or wax that may contain abrasives that could damage the finish.

For stainless steel: Aluminum polish may be used to polish small scratches and scuffs on the finish. Mild soap may be used also to clean the Taillight Guard.

For gloss black finishes: Mild soap may be used to clean the Taillight Guard.

(Driver Side Installation Shown)

