



## Installation Instructions for KC 74071 2-Tab Front Light Bar Jeep JK 2007-11

Thanks for choosing a KC HiLiTES product. We take pride in building the highest quality, best engineered systems possible. Your satisfaction with our product is important, so if you have any questions, please call our customer service line at 800-528-0950.

### Parts Included:

- 1 - Front Light Bar
- 2 - Mounting brackets
- 4 - 1/2" x 1 1/4" bolt
- 4 - 1/2" lock washer
- 4 - 1/2" nut
- 4 - 3/8" x 1" black bolt
- 4 - 3/8" black locking nut
- 4 - 3/8" black flat washer



### Installing the Bar

1. Locate the plastic filler panel between the bumper and the grill. This will need to be removed for the light bar installation. If you wish to reinstall the panel, it will have to be trimmed to fit.
2. Remove the two plastic screws in the top of the filler panel.
3. The panel can be easily removed by first sliding it forward under the bumper and then pulling up on the rear of the panel.
4. Note the bracket welded to each side of the frame rail. The light bar brackets will attach using the two lower bolt holes and the 1/2" hardware supplied.
5. Carefully slide the light bar brackets down between the grill and bumper. Align the holes in the light bar bracket with the two lower holes in the frame bracket.
6. Insert all four bolts from the inside of the frame bracket, then through the light bar bracket. Add the lock washers and start all four nuts on the bolts. (see photo)
7. Adjust the light bar brackets forward against the bumper and then loosely tighten all hardware.
8. Place the light bar between the two brackets and push all four black bolts through the holes in the bracket and bar. Add the flat washers on the inside and loosely attach all four nuts.
9. Align the bar so light tabs are level and tighten all hardware.



You're DONE! - - - - - Install your KC lights and enjoy.



IF YOU HAVE ANY PROBLEMS  
OR QUESTIONS, PLEASE CALL  
CUSTOMER SERVICE AT 800-528-0950