I - Sheet Number INS-HS75 Rev.C



Hood Shield

For proper installation and best possible fit, please read all instructions BEFORE you begin. For technical assistance or to obtain missing parts, please call Customer Relations at 1-800-344-8759.

Important Safety Information



- CAUTION Before driving, ensure that the hood shield is properly anchored to vehicle.
- Do not use automatic "brush-style" car washes.
- Do not use cleaning solvents of any kind.
- Periodically check all components for tightness.

Contents **NOTE:** Actual product may vary from illustration.









Hood Shield

Washer x2

Bump On x4

Tools Required











Car Wash Supplies

Clean Towel

Driver

Drill

Ratchet or Wrench


Preparation Before Painting / Installation

- A trial fit is recommended to ensure proper positioning and fit.
- Check fit of parts before painting as we will not accept the return of modified or painted parts.
- Wash your vehicle's hood to remove any debris and/or dirt.
- Dry the hood with a clean towel.

Installation Steps NOTE: Actual application may vary slightly from illustrations.



Open hood and remove (2) 8mm hex head screws located at the bottom of the metal grille brace on either side of the grille. Retain screws for later reinstallation.



Remove 8mm hex screws

Installation Steps **NOTE:** Actual application may vary slightly from drawings. Bring hood back down to a semi-closed posi-Carefully remove grille by grasping the top and bottom tion. Remove (7) grille retaining fasteners with of one side and gently pulling upwards. This will disena #2 phillips screwdriver, Retain fasteners for gage the top underside retention clips. Repeat the same later reinstallation procedure for the opposite side. The grille will need to be completely removed and placed carefully aside to avoid any possible damage. Clean this newly exposed area of the hood. **NOTE**: It may be necessary to squeeze the back side of these retainers by hand to help 2 3 the screw back out of the fastener base. Remove hood shield from packaging, fit hood shield onto Re-install the grille onto the hood, making sure that the hood at the wing mounting tabs first and then the center. protruding mounting points on the grille line up with Ensure the wing tabs are located on the underside of the the receiving holes in the hood. hood and that the center mounting tab cut outs do not block the existing hood holes. Make sure that the hood shield is centrally located on the hood. **NOTE:** the grille will not completely snap back into these mountings as the thickness of the 5 4 product will now hold it off slightly. Carefully open the hood and install the Reinstall the previously removed (7) fasteners back into the grille to ensure that it is screws and washers at the outer wing area being securely held in place. tabs to secure the hood shield to the hood. · 🔾 Washer Screw

NOTE: Do not over tighten.

6

Re-install the previously removed (2) 8mm hex head screws back into the bottom of the metal grille brace on either side of the grille. Close hood.

8

Care and Cleaning

• Wash only with mild soap & dry with a clean cloth.



The material that your product is made from can be recycled. Please also consider recycling the packaging that your product came in.



Congratulations!

You have purchased one of the many quality Husky® branded products. We take the utmost pride in our products and want you to enjoy years of satisfaction from your investment. We have made every effort to ensure that your product is top quality in terms of fit, durability, finish and ease of installation.

9



1-800-344-8759 • Visit us at huskyliners.com
© 2024 Husky Liners, Inc. All rights reserved.
Husky® and the Husky® logo are trademarks of Husky Liners, Inc.