



Specs/Features	
Rated Line Pull	12,500 Lbs
Motor	Series Wound 6.0 hp 12v DC
Switch	450A Sealed Contactor
Thermal Limiter	N/A
Controller	Wired Hand Control With 12' Lead (Wireless: part# 20156)
Power Unit	Multi-Mount / Remote Mountable
Battery Leads	6'
Gear Train	3 Stage Planetary
Gear Ratio	265:1
Gear Box	Clockable to Rotate Shifter (Contact BullDog for Instructions)
Clutch	Freespooling
Brake	Automatic Load Hold In Drum
Drum DIA x L	2.5" X 8.8" (63.5 X 223.5mm)
Overall Dimensions	21.7"L x 6.3"W x 8.6"H (552 x 160 x 218mm)
Mounting Bolt Pattern	10" x 4.5"
Warranty	2 Year Limited
Battery Recommendation	650CCA

Pull, Speed, Amps		
Line Pull Lbs	Line Speed Ft/Min	Current A
0	21.3	65
2000	11.5	126
4000	9.4	175
6000	7.9	230
8000	6.5	280
10000	5.8	355
12000	4.4	400

Line Pull & Rope Capacity in Layer		
Layer	Rated Line Pull Lbs	Total Rope on Drum Ft
1	12000	17
2	9210	41
3	8030	71
4	6894	90