



Specs/Features	
Rated Line Pull	12,500 Lbs
Motor	Premium Series Wound 6.0 hp 12v DC
Switch	500A Sealed For Superior Weather/Water Resistance
Thermal Limiter	Overheat Protection w/ LED Feedback Light & Auto Reconnect
Controller	Wired: Hand Control With 12' Lead Included (Wireless: part# 20156)
Power Unit	Remote Mountable
Battery Leads	6' w/ High Heat/Abrasion Resistant Sheathing
Gear Train	3 Stage Planetary
Gear Ratio	262:1
Gear Box	Clockable to Rotate Shifter (Contact BullDog Winch for Instructions)
Clutch	Freespooling
Brake	Automatic Load Hold In Drum
Drum DIA x L	2.5" X 9" (63 X 224mm)
Overall Dimensions	23"L x 6.7"W x 9.8"H (552 x 170 x 250mm)
Mounting Bolt Pattern	10" x 4.5"
Warranty	Limited Lifetime
Battery Recommendation	650CCA

Pull, Speed, Amps		
Line Pull Lbs	Line Speed Ft/Min	Current A
0	25.60	65
2000	12.50	100
4000	8.90	130
8000	7.30	200
10000	6.40	230
12500	6	290

Line Pull & Rope Capacity In Layer		
Layer	Rated Line Pull Lbs	Total Rope On Drum Ft
1	12500	15.75
2	10750	36.40
3	9460	61.30
4	8040	90