

⚠️ IMPORTANT

READ BEFORE YOU BEGIN INSTALLATION

IT IS CRITICAL FOR YOUR SAFETY THAT YOU CAREFULLY READ AND FOLLOW THE SAFETY CAUTIONS AND INSTALLATION INSTRUCTIONS BOTH PRIOR TO AND DURING INSTALLATION.

USER SAFETY CAUTION

During installation, be mindful of the potential for sharp edges on the product or vehicle. Taking proper safety precautions helps ensure a safe and smooth installation process.



Always wear protective gloves and handle components with care to reduce the risk of injury.

TEMPERATURE SURFACE CAUTION

During high temperatures or extended sun exposure, surfaces of this product may become hot to the touch, posing a risk of burns or injury. Use caution when handling the product in hot weather and allow time for it to cool before contact.



Always check surface temperature before use to ensure safe handling conditions.

FASTENER TORQUE CAUTION

All fasteners must be tightened to the specified torque values provided in the installation instructions to ensure proper fit and safe operation of the tonneau cover. Under- or over-tightening can lead to product failure, potential damage to your vehicle, injury, or safety hazards while driving.



Always use a calibrated torque wrench and follow the specifications in the installation instructions.

PINCH POINT SAFETY CAUTION

This tonneau cover may create pinch points when closing or operating near solid surfaces such as the truck bed rails or tailgate. To prevent injury, keep hands, fingers, and other body parts clear of moving parts during operation.



Always operate the cover slowly and with caution to ensure safe and proper use.

! IMPORTANT

READ BEFORE YOU BEGIN INSTALLATION

IT IS CRITICAL FOR YOUR SAFETY THAT YOU CAREFULLY READ AND FOLLOW THE SAFETY CAUTIONS AND INSTALLATION INSTRUCTIONS BOTH PRIOR TO AND DURING INSTALLATION.

ENTRAPMENT SAFETY WARNING

This tonneau cover does not feature a manual release mechanism from inside the truck bed. To prevent the risk of entrapment, never allow anyone to be inside the bed of the truck when the cover is closed.



Always ensure the area is clear before closing the cover, and keep the cover securely latched when not in use to avoid accidental closure.

COVER ATTACHMENT WARNING

A partially folded up or unsecured cover may detach during transit, risking vehicle or property damage and personal injury.



Always verify the tonneau cover is properly secured before operating the vehicle.

CARGO TRANSPORT WARNING

When transporting cargo that is taller than the truck bed, the cover must be fully folded open and securely fastened with both retainer straps. An unsecured cover can detach while driving, risking vehicle or property damage and personal injury.



Never operate the vehicle with a partially folded up cover.

COVER POSITION WARNING

Before operating the vehicle, always verify the tonneau cover is either fully folded open and secured with both buckles or fully folded closed and securely latched down.



Never operate the vehicle if the tonneau cover is not properly secured.

Any damaged or missing parts?

Parts will be shipped to you directly.



Call 800-877-2588, Mon - Fri, 8:30 a.m. - 6:00 p.m. EST

**PARTS INCLUDED
IN YOUR KIT**

- A** 1x Cover assembly
- B** 4x Clamp brackets
- C** 4x Clamp brackets
- D** 8x Torx screws
- E** 8x Torx screws



TOOLS REQUIRED

- Scissors or razor blade




NOTE: It is important that all areas where the bed cover mounts are clean and free of debris prior to installing.


1 Place the assembled bed cover assembly (A) over the cab end of the truck bed. **NOTE:** Take care not to damage or deform the seals when installing the bed cover onto the truck bed. Visually check to ensure the front bed cover frame is even on both sides and square with the bed. Make sure the cover is centered on the bed of the vehicle before tightening clamps.




2 Unfold the bed cover assembly (A) fully and adjust its position over the truck bed for proper front (cab) and rear (tailgate) alignment. When positioned front and back, the tailgate seal should contact the tailgate with the two fins, as shown in the section. Then carefully refold the bed cover without shifting its position on the truck bed.




3 If there are cargo rail end caps remove the rear (tailgate) end. Remove any tie-downs. Do this for both sides of the truck bed.




4 Install the cab slide nut (C) into the rear (tailgate) end of the cargo rail. Position near the cab. Align the cab clamp bracket (B) with the cab clamp of the bed cover. Use two Torx screws (D) to mount the cab clamp bracket (B) to the cab slide nut (C). Tighten the screws with the T-27 Torx key (E). Do this for both sides of the truck bed.




5 Hook the cab clamp under the cab clamp bracket (B) and tighten the T-handle until it contacts the bracket (B), then tighten two more turns. Do this for both sides of the truck bed.




6 The tether comes assembled on the cab bow of the bed cover. Unscrew the knob from the slide nut and separate the nut, knob and washer.





7 Insert tether slide nut into the rear of the cargo rail and position about three inches from the front bracket. Reassemble the tether by threading the knob through the washer and into the slide nut. Install the tether on both sides of the truck bed. Tighten the knob securely so that the tether clamp does not slide/shift or lift from the truck bed flange.



8 Reinstall any tie-down cleats and the end cap on both sides of the truck bed.




9 Install the tailgate slide nut (C) into the rear (tailgate) end of the cargo rail. Position near the tailgate. Align the clamp bracket (B) with the tailgate clamp of the bed cover. Use two Torx screws (D) to mount the tailgate clamp bracket (B) to the slide nut (C). Tighten the screws with the T-27 Torx key (E). Do Not Overtighten. Do this for both sides of the truck bed.





! Torque fasteners to 65 in-lb (7.3 Nm)

10 With the tailgate open, completely close the bed cover.



11 Slide the rear clamp out to the bed wall. Pull the rear clamp down, and hook it under the bottom edge of the metal bed flange. Do this for both the driver and passenger side.






Rear View Section

DRIVING WITH THE TONNEAU OPEN

Release the rear clamps and fold the tonneau forward.

! **IMPORTANT:** Before folding the second section of the tonneau, the rear clamps must be stowed into the rail to prevent damage to the fabric. Failure to stow the handle will puncture the tarp and void the warranty.


! Fold the tonneau forward and fasten the straps in the middle section to the front rail. Check that the straps are tight. **Failure to do so could allow the wind to blow the cover back resulting in damage to the cover and truck.**



! IMPORTANT

Re-tighten the front/cab clamps and tethers after the first week of driving the vehicle. Also periodically check the clamps and tethers to ensure they are secure.

Closed/Extended Position – Bed cover must be completely secured by all four (4) clamps.
Open/Folded Position – Bed cover must be completely folded up (all panels) and secured at the cab with the provided buckles straps and with both tethers attached.
Do NOT drive with the bed cover in a partially open position.




NOTE: The tarp cannot be removed from the aluminum frame. Attempting to do so will cause damage and void the warranty.

Do NOT allow the vehicle to be towed backwards without first removing the cover from the vehicle.

Remove any snow or foreign matter before folding the bed cover.

REPLACEMENT PARTS

NOTE: To order replacement parts, it is best to contact our Customer Service Department for assistance to ensure that you get the correct part for your vehicle application. When ordering, xxx represents the 3 digit suffix, as referenced on the sales receipt or vehicle application list.



Call Out	Title	Part Number	Description	Model Year	Qty
A	Cab Seal	32270600	Cut to fit		1
B	Tail Seal	32562569	Seal - tail 2 fin with adhesive		1
C	Side Seal	32520052	Bulb seal		1
D	Corner	24520100	Corner only, used front or rear		1
E	Corner Pad	32520002	Pad only, used front or rear, 1/2" thick		1
F	Tailgate Hinge Assembly	35521033			1
G	Cab Hinge Assembly	35521032			1
H	Cab Clamp Assembly	1034			1
I	Tailgate Clamp Assembly	1035/1042			1
J	Short Tarp Tie Down Strap	54440400	Short Tie Down Strap w/Male Buckle, used with 4-bow configuration		1
K	Long Tarp Tie Down Strap	54720400	Long Tie Down Strap w/Male Buckle, used with 3-bow configuration		1
L	Buckle Assembly	54440100	Single Buckle assembly w/Female Buckle for Tie-down strap		1
M	Bracket Kit	22000014	Purple clamp pack #14		1

LIMITED WARRANTY

WARRANTY COVERAGE

This truck bed cover is warranted against defects in materials or workmanship as follows. This warranty is void if the product has been damaged in an accident, or due to neglect, unforeseeable use, improper installation, improper servicing, or other cause not arising out of defects in material or workmanship.

LIMITED FIVE-YEAR WARRANTY ON HARD PARTS

All hardware included with your truck bed cover, including rails, clamps and bows carry a limited warranty for five (5) years from the original date of purchase, subject to the terms below.

LIMITED FIVE-YEAR WARRANTY FOR FABRIC

The fabric on your truck bed cover carries a limited warranty for five (5) years from the original date of purchase, subject to the terms below.

WARRANTY IS NOT TRANSFERABLE

The warranty is to the initial consumer purchasing the truck bed cover and it is not transferrable to a subsequent end user. Proof of purchase may be required to enforce these warranty rights.

FAILURE TO FOLLOW THESE CARE AND USE INSTRUCTIONS WILL VOID THE WARRANTY

- Clean with mild automotive soap and water only.
- Use only water-based vinyl conditioners. Use of vinyl conditioners that contain silicone or petroleum may crack and shrink the vinyl and will void the warranty.
- Prior to vehicle operation, all clamps and retention mechanisms must be tightly secured to the vehicle:
 - **Closed/Extended Position** – Bed cover must be completely secured by all four (4) clamps.
 - **Open/Folded Position** – Bed cover must be completely folded up (all panels) and secured at the cab with the provided buckles straps and with both tethers attached. Do NOT drive with the bed cover in a partially open position!
- The truck bed cover MUST be free of foreign material, including snow and ice, before opening.
- Rear/tailgate panel clamps must be properly stored prior to folding the cover in order to prevent damage to the fabric.
- Front/cab clamps and retention mechanisms must be checked for tightness after a week of driving following installation (or re-installation) of the truck bed cover and periodically thereafter.
- Do NOT allow the vehicle to be towed backwards without first removing the cover from the vehicle.

WARRANTY PERFORMANCE

If all warranty conditions are met, a defective truck bed cover, tarp, or hardware component will either be repaired or replaced (at our option). We reserve the right, for any warranted return, to substitute a newer model of bed cover having similar form and function, to offer a warranty discount on an entire replacement system, and/or provide remedies other than those mentioned in this document.

WARRANTY PROCESS

A Return Authorization number must be obtained from our Customer Service Department prior to returning any product. We may require the original item to be returned postage prepaid for final determination. Shipping charges will apply for any repair or replacement. Other than postage or shipping charges, no charge will be made for repair or replacement under this warranty.

This warranty gives you specific legal rights. As a consumer, you may also have additional rights and remedies under the laws of your state.

WARRANTY REGISTRATION

Warranty registration must be on file and/or proof of original purchase (detailed and dated receipt) required for warranty to be effective.

Register online at <https://realtruck.com/extang-warranty>

**REGISTER
YOUR
WARRANTY
ONLINE**



SOMETHING DAMAGED? MISSING PARTS?

CALL US FIRST
800-877-2588

WE CAN HELP YOU QUICKLY AND EASILY OVER THE PHONE

Experienced Customer Service staff are available
to answer all your truck bed cover questions

CUSTOMER SERVICE HOURS

8:30 a.m. TO 6:00 p.m. EST, MONDAY - FRIDAY

Truck bed cover model: _____

Purchase date: _____

Lot code: _____

Lot code can be found on the underside of cover.