

I-SHEET PART NUMBER: INST-00298 PART NUMBER: **315417722** PRODUCT: **RS HOOP STEP** APPLICATION: **15-21 F-150 QC**

HARDWARE DESCRIPTION		QTY.
HWKT-00031X		
FLNT- 00696X	M8-1.25 CLASS 8 SERRATED FLANGE NUT	12
FDRW- 00736X	M8 FENDER WASHER	12
	M8 Carriage bolt	8
	M8 Flanged hex nut	8
PARTS INCLUDED		QTY
DRIVER SIDE STEP		1
PASSENGER SIDE STEP		1
MOUNTING BRACKET		4



<u>Step 1</u>: Identify driver side step.



<u>Step 2.</u> Install the (x6) mounting brackets to each attachment point on the main tube using the supplied M10x25 carriage bolts, M10 hex nuts and leave loose for now. <u>Note the</u> <u>bracket orientation for driver and passenger.</u>



<u>Step 3:</u> Remove all 8mm flange nuts from the 8mm factory threaded studs to remove the OE running boards.





I-SHEET PART NUMBER: INST-00298 PART NUMBER: **315417722** PRODUCT: **RS HOOP STEP** APPLICATION: **15-21 F-150 QC**

<u>Step 4:</u> Next, carefully raise the step assembly into position and align the three brackets with the nine 8mm OE threaded studs.

<u>Step 5:</u> Using the supplied 8mm flanged nuts, fasten all nine mounting positions. Leave loose at this time.

Step 6: Beginning at the rear bracket, push upwards on the tube to align with the body then tighten only the lower rear fastener at this time.

<u>Step 7:</u> Next, move to the front bracket, push upwards on the tube to level with the body. Tighten all three fasteners.

<u>Step 8:</u> Tighten the remaining fasteners on rear bracket.



<u>Step 9.</u> Next, tighten brackets (x2) at the main tube. **<u>Step10.</u>** Repeat steps 3-8 for passenger side.

