





Part #11116.06

460 HORIZON DR. SUITE 400 | SUWANEE, GA 30024 | PHONE: 770-614-6101 | FAX: 770-614-6069 | info@omix-ada.com

# Hood Catch Kit, JK



### **Components**

1. Upper Catch(2)	5. Lower Catch Assembly(2)
2. Upper Catch Gasket(2)	6. Lower Catch Gasket(2)
3. Upper Catch Screw Plate(2)	7. Lower Catch Lock Nut(2)
4. Upper Catch Lock Nuts(4)	

NOTE: Only one side is pictured.

#### **OMIX-ADA® TECHNICAL SUPPORT**

**PHONE**: M-F 8am - 5pm EST 1-800-449-6649 | **EMAIL**: techsupport@omix-ada.com

FOR WARRANTY INFORMATION VISIT: www.Omix-Ada.com







460 HORIZON DR. SUITE 400 | SUWANEE, GA 30024 | PHONE: 770-614-6101 | FAX: 770-614-6069 | info@omix-ada.com

# Hood Catch Kit, JK

1. Pre-assemble the components.



2. Remove OE Hood Catches.



3. Remove Rubber Bumper from OE Hood Catch.









460 HORIZON DR. SUITE 400 | SUWANEE, GA 30024 | PHONE: 770-614-6101 | FAX: 770-614-6069 | info@omix-ada.com

## Hood Catch Kit, JK

4. Install OE Rubber Bumper onto Stainless Hood Catch like shown below. Install Hood Catch onto vehicle where OE pieces were removed, making sure to install included gaskets under the pieces to protect paint.





5. Tighten all hardware. Close hood and latch Stainless Hood Catches.

