

45415

09-10 DODGE
CHALLENGER



45415

09-10 DODGE
CHALLENGER

09-10 DODGE CHALLENGER

Sport Series Bumper Grille

TOOLS REQUIRED:

Flathead Screwdriver
10mm & 1/2" Sockets
Ratchet

PARTS LIST

(3) 2" Flange Brackets
(3) 6/32" Nylon Lock Nuts
(3) 2 3/4" Threaded "J" Hooks
(1) Bumper Grille

Step 1

PLEASE READ AND UNDERSTAND ALL INSTRUCTIONS BEFORE ATTEMPTING INSTALLATION. Remove the plastic cover from under the front of the vehicle, this gives you access to the underside of the front bumper. There are 9 plastic pop clips, (8) 10mm screws and (2) 1/2" Bolts. (Fig 1)

Step 2

Insert the mesh grille into the opening in the factory bumper. (Fig 2)

Step 4

The 3 threaded "J" hooks will be inserted through the mesh and hook onto the mesh. (Fig 3) They install onto the 2 corners of the grille and in the center of the grille. The threaded ends will go through the black plastic of the factory bumper.

Step 5

From underneath the car reach up behind the bumper opening and install one of the small brackets and a 6/32" lock nut onto the screw with the bracket tapered ends facing the front of the vehicle. Repeat for the remaining 2 screws. (Fig 4) Reinstall the plastic cover under the vehicle. Installation is now complete.

